

# LEVELtrol II

## Multi-Function Level Indicator, Controller and Batcher

Flow Instruments  
PROCESS & LEVEL MONITORS

### Features

- Level and Tank Volume/Mass Indicator
- Batching by Level
- Level Control, Tank Volume, Corrected Volume and Mass Calculations
- Menu Selectable Hardware & Software Features
- Two Line LCD, OLED or VFD Display
- Isolated Outputs Standard
- RS-232 Port Standard
- RS-485 Modbus RTU Optional
- Windows™ Setup Software
- DIN Enclosure with Two Piece Connectors
- DDE Server & HMI Software Available
- Panel Mount or Wall Mount Enclosure

### Description:

The LEVELtrol II Flow Computer satisfies the instrument requirements for a variety of level sensor types in liquid applications. Multiple tank geometries, fluid equations and instrument functions are available in a single unit with many advanced features.

The alphanumeric display shows measured and calculated parameters in easy to understand format. Single key direct access to measurements and display scrolling are supported

The versatility of the LEVELtrol II permits a wide measure of versatility within the instrument package. The various hardware inputs and outputs can be "soft" assigned to meet a variety of common application needs. The user "soft selects" the usage of each input/output while configuring the instrument. Consider the following illustrative examples.

The isolated analog output can be chosen to follow level, tank volume, corrected tank volume, tank mass, temperature, or density by means of a menu selection. Most hardware features are assignable by this method.

The user can assign the standard RS-232 Serial Port for data logging, transaction printing, or for connection to a modem for remote meter reading. Setup software is supplied for easy programming and monitoring using a PC

### Specifications:

#### Environmental

- Operating Temperature: 0°C to +50°C
- Storage Temperature: -40°C to +85° C
- Humidity : 0-95% Non-condensing
- Materials: U.L. approved

**Listing:** UL/C-UL Listed (File No. E192404), CE Compliant

#### Display

- Type: 2 lines of 20 characters
- Types: Backlit LCD, OLED and VFD ordering options
- Character Size: 0.2" nominal
- User programmable label descriptors and units of measure



### Keypad

- Keypad Type: Membrane Keypad with 16 keys
- Keypad Rating: Sealed to NEMA 4X / IP65

### Enclosure

- Style: See Ordering Code for Available Mounting Options
- Size: See Dimensions
- Depth behind panel: 6.5" including mating connector
- Type: DIN
- Materials: Plastic, UL94V-0, Flame retardant
- Bezel: Textured per matt finish

### Power Input

- The factory equipped power option is internally fused. An internal line to line filter capacitor and MOV are provided for added transient suppression.
- 110 VAC Power Option: 85 to 127 Vrms, 50/60 Hz
- 220 VAC Power Option: 170 to 276 Vrms, 50/60 Hz
- DC Power Option:
  - 12 VDC (10 to 14 VDC)
  - 24 VDC (14 to 28 VDC)
- Power Consumption
  - AC Power: 11.0 V/A (11W)
  - DC Power: 300 mA max.

### Level Inputs:

#### Analog Input:

- Accuracy: 0.01% FS at 20° C
- Ranges
  - Voltage: 0-10 VDC, 0-5 VDC, 1-5 VDC
  - Current: 4-20 mA, 0-20 mA
- Basic Measurement Resolution: 16 bit
- Update Rate: 4 updates/sec
- Automatic Fault detection: Signal over/under-range, Current Loop Broken
- Calibration: Software Calibration (no trimmers) and Auto-zero Continuously
- Extended calibration: Learns Zero and Full Scale of each range using special test mode.

**Sensor Types Supported:**

Differential Pressure, Ultrasonic, Many Others

**Tank Geometries:**

Horizontal, vertical, spherical and 32 point strapping table

**Auxiliary / Compensation Input**

The auxiliary/compensation input is menu selectable for temperature, density or not used. This input is used for the compensated input when performing compensated tank volume and mass calculations. It can also be used as a general purpose input for display and alarming.

Available Input Ranges

Voltage: 0-10 VDC, 0-5 VDC, 1-5 VDC

Current: 4-20 mA, 0-20 mA

Resistance: 100 Ohms DIN RTD

**Control Inputs**

Switch Inputs are menu selectable for Start, Stop, Reset, Lock, Alarm Acknowledge, Print or Not Used.

**Relay Outputs**

The relay outputs are menu assignable to Level, Tank Volume, Temperature, Density, Batch Control or Malfunction

Number of relays: 2 (4 optional)

Contact Ratings: 5 amp, 240 VAC or 30 VDC

**Isolated Analog Output**

The analog output is menu assignable to correspond to the Level, Tank Volume/Mass, Temperature or Density.

Type: Isolated 4-20 mA Current Sourcing

**Excitation Voltage (AC powered units only)**

24 VDC @ 100 mA (fault protected)

**Isolated Pulse output**

The isolated pulse output is menu assignable to generate pulse outputs when tank fills, empties or both.

Pulse Output Form: Isolated Photomos Relay

Maximum On Current: 25 mA

Maximum Off Voltage: 30 VDC

Pulse Duration: 10 msec or 100 msec

**Serial Communication**

The serial port can be used for printing, datalogging, modem connection and communication with a computer. Windows setup software is included for easy programming using a PC.

RS-232:

Device ID: 01-99

Baud Rates: 300, 600, 1200, 2400, 4800, 9600, 19200

Parity: None, Odd, Even

Handshaking: None, Software, Hardware

Print Setup: Configurable print list and formatting

RS-485:

Device ID: 01-247

Baud Rates: 300, 600, 1200, 2400, 4800, 9600, 19200

Parity: None, Odd, Even

Protocol: Modbus RTU (Half Duplex)

**Real Time Clock**

LEVELtrol II is equipped with a battery backed real time clock with display of time and date.


Format:

12 or 24 hour time display

Day, Month, Year date display


**Tank Level/ Volume Applications:**

The LEVELtrol-II can monitor actual liquid level and tank volume of a liquid. Alarms are provided via relays and datalogging is available via analog (4-20mA) and serial outputs.



**Corrected Liquid Volume Applications:**

Monitoring corrected volume of a liquid stored in a horizontal tank. Alarms are provided via relays and datalogging is available via analog (4-20mA) and serial outputs.



**Liquid Mass Applications:**

Monitoring level and mass total of any liquid in a tank. Alarms are provided via relays and datalogging is available via analog (4-20mA) and serial outputs.

